

OSCI Exercises

C++ crash course

Winter term 2026/27

Manuel Vögele & Benedict Herzog

Bochum Operating Systems and System Software Group (BOSS)

RUHR
UNIVERSITÄT
BOCHUM

RUB



From: Linus Torvalds
Subject: Re: Compiling C++ kernel module + Makefile
Date: Mon, 19 Jan 2004 22:46:23 -0800 (PST)

On Tue, 20 Jan 2004, Robin Rosenberg wrote:

>
> This is the "We've always used COBOL^H^H^H" argument.

In fact, in Linux we did try C++ once already, back in 1992.

It sucks. Trust me - writing kernel code in C++ is a BLOODY STUPID IDEA.

The fact is, C++ compilers are not trustworthy. They were even worse in 1992, but some fundamental facts haven't changed:

- the whole C++ exception handling thing is fundamentally broken. It's _especially_ broken for kernels.
- any compiler or language that likes to hide things like memory allocations behind your back just isn't a good choice for a kernel.
- you can write object-oriented code (useful for filesystems etc) in C, _without_ the crap that is C++.

In general, I'd say that anybody who designs his kernel modules for C++ is either

- (a) looking for problems
- (b) a C++ bigot that can't see what he is writing is really just C anyway
- (c) was given an assignment in CS class to do so.

Feel free to make up (d).

Linus

C++: As Close as Possible to C, but no Closer

Andrew Koenig and Bjarne Stroustrup, The C++ Report. July 1989

ANSI C is (almost) valid C++

```
#include <stdio.h>
```

```
int main() {  
    const char * str = "Computer_Science";  
    int n = 4;  
    printf("%s_ %d\n", str, n);  
    return 0;  
}
```

```
#include <stdio>
```

```
int main() {  
    const char * str = "Computer_Science";  
    int n = 4;  
    printf("%s_ %d\n", str, n);  
    return 0;  
}
```

```
#include <iostream>
```

```
int main() {  
    const char * str = "Computer_Science";  
    int n = 4;  
    std::cout << str << ' ' << n << std::endl;  
    return 0;  
}
```

```
#include <iostream>
```

```
int main() {  
    const std::string str = "Computer_Science";  
    int n = 4;  
    std::cout << str << ' ' << n << std::endl;  
    return 0;  
}
```

```
#include <iostream>
using namespace std;

int main() {
    const string str = "Computer_Science";
    int n = 4;
    cout << str << ' ' << n << endl;
    return 0;
}
```

Namespaces

```
namespace Foo {  
    int getNum() {  
        return 23;  
    }  
}
```

```
namespace Bar {  
    int getNum() {  
        return 42;  
    }  
}
```

```
std::cout << Foo::getNum() << std::endl  
          << Bar::getNum() << std::endl;
```

References

```
int foo = 23;  
int &bar = foo;  
std::cout << bar << std::endl; // Output: 23
```

```
bar = 42;  
std::cout << foo << std::endl; // Output: 42
```

References

```
int foo = 23;  
int &bar = foo;  
std::cout << bar << std::endl; // Output: 23
```

```
bar = 42;  
std::cout << foo << std::endl; // Output: 42
```

Differences to Pointers

- initialization at definition
- automatically dereferenced
- cannot be changed
- cannot be NULL

References as function parameters

Constant references

```
void dump(std::ostream &os, const Complex &c) {  
    os << c.real << " + " << c.img << "i\n";  
}
```

References as function parameters

Constant references

```
void dump(std::ostream &os, const Complex &c) {  
    os << c.real << " + " << c.img << "i\n";  
}
```

mutable references

```
void inc(int& i) { i++; }
```

```
int foo = 23;  
inc(foo);
```

```
std::cout << foo << std::endl; // Output: 24
```

Default Parameter Values

```
void inc(int& i, int n = 1) {  
    i += n;  
}
```

```
int foo = 23;  
inc(foo);
```

```
std::cout << foo << std::endl; // Output: 24
```

```
inc(foo, 2);
```

```
std::cout << foo << std::endl; // Output: 26
```

Function Overloading

```
bool isZero(int i){  
    return i == 0;  
}
```

```
bool isZero(double i){  
    const double eps = 0.00001;  
    return i < eps && i > -eps;  
}
```

Function Overloading

```
bool isZero(int i){  
    return i == 0;  
}
```

```
bool isZero(double i){  
    const double eps = 0.00001;  
    return i < eps && i > -eps;  
}
```



Overload resolution is not trivial!

```
struct Disp {  
    char val;  
    int x, y;  
};
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    struct Disp p;  
    p.val = 'X';  
    p.x = 2;  
    p.y = 0;  
    cout << p.val << endl;  
}
```

```
// Geht in C++ nicht:  
// struct Disp p = {  
//     .val = 'X',  
//     .x = 2,  
//     .y = 0  
// }
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp() {  
        val = 'X';  
        this->x = 2;  
        this->y = 0;  
    }  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p;  
    cout << p.val << endl;  
}
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp(char c, int x=0, int y=0) {  
        val = c;  
        this->x = x;  
        this->y = y;  
    }  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p('X', 2);  
    cout << p.val << endl;  
}
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp(char c, int x=0, int y=0) {  
        val = c;  
        this->x = x;  
        this->y = y;  
    }  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p{'X', 2};  
    cout << p.val << endl;  
}
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp(char c, int x=0, int y=0)  
        : val(c), x(x), y(y) {}  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p{'X', 2};  
    cout << p.val << endl;  
}
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp(char c, int x=0, int y=0)  
        : val(c), x(x), y(y) {}  
  
    Disp(int p) : val('X'),  
                x(p % 80), y(p / 80) {}  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p{2};  
    cout << p.val << endl;  
}
```

disp.h:

```
struct Disp {  
    char val;  
    int x, y;  
  
    Disp(char c, int x=0, int y=0)  
        : val(c), x(x), y(y) {}  
  
    Disp(int p)  
        : Disp('X', p % 80, p / 80) {}  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p{2};  
    cout << p.val << endl;  
}
```

disp.h:

```
int count = 0;
struct Disp {
    char val;
    int x, y;

    Disp(char c, int x=0, int y=0)
        : val(c), x(x), y(y) {
        count++;
    }

    Disp(int p)
        : Disp('X', p % 80, p / 80) {}

    ~Disp() { count--; }
};
```

disp.cc:

```
#include "disp.h"
using namespace std;

void func() {
    Disp p{2};
    cout << p.val << "-"
         << count << endl;
}
```

disp.h:

```
struct Disp {
    static int count;
    char val;
    int x, y;

    Disp(char c, int x=0, int y=0)
        : val(c), x(x), y(y) {
        count++;
    }

    Disp(int p)
        : Disp('X', p % 80, p / 80) {}

    ~Disp() { count--; }
};
```

disp.cc:

```
#include "disp.h"
using namespace std;

void func() {
    Disp p{2};
    cout << p.val << "-"
         << Disp::count << endl;
}

int Disp::count = 0;
```

disp.h:

```
struct Disp {
    static int count;
    char val;
    int x, y;

    Disp(char c, int x=0, int y=0);

    Disp(int p)
        : Disp('X', p % 80, p / 80) {}

    ~Disp();
};
```

disp.cc:

```
#include "disp.h"
using namespace std;

void func() {
    Disp p{2};
    cout << p.val << "-"
         << Disp::count << endl;
}

int Disp::count = 0;

Disp::Disp(char c, int x, int y)
    : val(c), x(x), y(y) {
    count++;
}

Disp::~Disp() { count--; }
```

disp.h:

```
struct Disp {  
    private:  
        static int count;  
        char val;  
        int x, y;  
  
    public:  
        Disp(char c, int x=0, int y=0);  
        Disp(int p);  
        ~Disp();  
};
```

disp.cc:

```
#include "disp.h"  
using namespace std;  
  
void func() {  
    Disp p{2};  
    // Compiler error at:  
    cout << p.val << endl;  
  
    int Disp::count = 0;  
  
    Disp::Disp(char c, int x, int y)  
        : val(c), x(x), y(y) {  
        count++;  
    }  
  
    Disp::~Disp() { count--; }
```

```
class Disp {  
    private:  
        static int count;  
        char val;  
        int x, y;  
  
    public:  
        Disp(char c, int x=0, int y=0);  
        Disp(int p);  
        ~Disp();  
};
```

```
class Disp {  
    static int count;  
    char val;  
    int x, y;  
  
public:  
    Disp(char c, int x=0, int y=0);  
    Disp(int p);  
    ~Disp();  
};
```

Unterschied Standardsichtbarkeit

`public` bei struct (und union)

`private` bei class

```
struct Foo {  
    Foo(int i) { ... };  
    test() { ... };  
};
```

```
Foo foo1{23};  
foo1.test(); // OK
```

```
Foo foo2(23);  
foo2.test(); // OK
```

```
struct Bar {  
    Bar() { ... };  
    test() { ... };  
};
```

```
Bar bar0;  
bar0.test(); // OK
```

```
Bar bar1{};  
bar1.test(); // OK
```

```
Bar bar2();  
bar2.test(); // Fehler
```

```
struct Foo {  
    Foo(int i) { ... };  
    test() { ... };  
};
```

```
Foo foo1{23};  
foo1.test(); // OK
```

```
Foo foo2(23);  
foo2.test(); // OK
```

```
struct Bar {  
    Bar() { ... };  
    test() { ... };  
};
```

```
Bar bar0;  
bar0.test(); // OK
```

```
Bar bar1{};  
bar1.test(); // OK
```

```
Bar bar2();  
bar2.test(); // Fehler
```

error: request for member 'test' in 'bar2',
which is of non-class type 'Bar()'

```
struct Foo {  
    Foo(int i) { ... };  
    test() { ... };  
};
```

```
Foo foo1{23};  
foo1.test(); // OK
```

```
Foo foo2(23);  
foo2.test(); // OK
```

```
struct Bar {  
    Bar() { ... };  
    test() { ... };  
};
```

```
Bar bar0;  
bar0.test(); // OK
```

```
Bar bar1{};  
bar1.test(); // OK
```

```
Bar bar2();  
bar2.test(); // Fehler
```

**error: request for member 'test' in 'bar2',
which is of non-class type 'Bar()'**

→ Frequent error dubbed „most vexing parse“!

Inheritance

Syntax: `class <Derived>: <inheritance type> <Base>`

Inheritance

Syntax: `class <Derived>: <inheritance type> <Base>`

```
class Foo {  
    int n;  
    protected:  
        int f1(int i){  
            return i * n;  
        }  
};
```

Inheritance

Syntax: `class <Derived>: <inheritance type> <Base>`

```
class Foo {  
    int n;  
    protected:  
        int f1(int i){  
            return i * n;  
        }  
};
```

```
class Bar : Foo {  
    public:  
        int n; // custom variable  
        int f2(int i){  
            return f1(i) * n;  
        }  
};
```

Inheritance

Syntax: `class <Derived>: <inheritance type> <Base>`

```
class Foo {  
    int n;  
    protected:  
        int f1(int i){  
            return i * n;  
        }  
};
```

```
class Bar : Foo {  
    public:  
        int n; // custom variable  
        int f2(int i){  
            return f1(i) * n;  
        }  
};
```

inheritance type	Elements from Base
public	element's visibility unchanged <i>Default if Derived is a struct</i>
protected	public elements from Base become protected
private	public and protected elements from Base become private <i>Default if Derived is a class</i>

Multiple Inheritance

```
class FooBaz: public Foo, protected Baz
{
    // ...
}
```

Multiple Inheritance

```
class FooBaz: public Foo, protected Baz
{
    // ...
}
```

If Foo and Baz have the same base class → Diamond-Problem

Methodselection

non-virtual at compile time based on the static type

virtual at runtime based on the „actual“ type

Virtual Methods

```
class Foo {
public:
    void f1() { cout << "Foo::f1" << endl; };
    virtual void f2() { cout << "Foo::f2" << endl; };
    virtual void f3() = 0;
};

class Bar : public Foo {
public:
    void f2() { cout << "Bar::f2" << endl; }
    void f3() { cout << "Bar::f3" << endl; }
};

class Baz : public Foo {
public:
    void f1() { cout << "Baz::f1" << endl; }
    void f3() { cout << "Baz::f3" << endl; }
};
```

Virtual Methods

```
class Foo {
public:
    void f1() { cout << "Foo::f1" << endl; };
    virtual void f2() { cout << "Foo::f2" << endl; };
    virtual void f3() = 0;
};

class Bar : public Foo {
public:
    void f2() override { cout << "Bar::f2" << endl; };
    void f3() override { cout << "Bar::f3" << endl; };
};

class Baz : public Foo {
public:
    void f1() { cout << "Baz::f1" << endl; };
    void f3() override { cout << "Baz::f3" << endl; };
};
```

Virtual Methods

```
class Foo {
    public:
        void f1() {...};
        virtual void f2() {...};
        virtual void f3() = 0;
};
class Bar : public Foo {
    public:
        void f2() override {...}
        void f3() override {...}
};
class Baz : public Foo {
    public:
        void f1() {...}
        void f3() override {...}
};
```

```
Foo foo;
// Nicht erlaubt
// Übersetzerfehler
```

Virtual Methods

```
class Foo {  
    public:  
        void f1() {...};  
        virtual void f2() {...};  
        virtual void f3() = 0;  
};  
class Bar : public Foo {  
    public:  
        void f2() override {...}  
        void f3() override {...}  
};  
class Baz : public Foo {  
    public:  
        void f1() {...}  
        void f3() override {...}  
};
```

```
Bar bar;  
bar.f1();  
// "Foo::f1"  
bar.f2();  
// "Bar::f2"  
bar.f3();  
// "Bar::f3"
```

Virtual Methods

```
class Foo {  
    public:  
        void f1() {...};  
        virtual void f2() {...};  
        virtual void f3() = 0;  
};  
class Bar : public Foo {  
    public:  
        void f2() override {...}  
        void f3() override {...}  
};  
class Baz : public Foo {  
    public:  
        void f1() {...}  
        void f3() override {...}  
};
```

```
Bar bar;  
bar.f1();  
// "Foo::f1"  
bar.f2();  
// "Bar::f2"  
bar.f3();  
// "Bar::f3"  
  
Baz baz;  
baz.f1();  
// "Baz::f1"  
baz.f2();  
// "Foo::f2"  
baz.f3();  
// "Baz::f3"
```

Virtual Methods

```
class Foo {
    public:
        void f1() {...};
        virtual void f2() {...};
        virtual void f3() = 0;
};
class Bar : public Foo {
    public:
        void f2() override {...}
        void f3() override {...}
};
class Baz : public Foo {
    public:
        void f1() {...}
        void f3() override {...}
};
```

```
Foo * foo = &bar;
foo->f1();
// "Foo::f1"
foo->f2();
// "Bar::f2"
foo->f3();
// "Bar::f3"

foo = &baz;
foo->f1();
// "Foo::f1"
foo->f2();
// "Foo::f2"
foo->f3();
// "Baz::f3"
```

Operator Overloading & friends

```
class Complex {
    int real, img;
public:
    Complex(int real, int img) : real(real), img(img) { }

    Complex operator+(const Complex &o) {
        return Complex{real + o.real, img + o.img};
    }

    friend Complex operator-(Complex l, Complex r);
};

Complex operator-(Complex l, Complex r) {
    return Complex{l.real - r.real, l.img - r.img};
}

std::cout << Complex{4,2} - Complex{2,1} << std::endl;
```

Operator Overloading – usage in STuBS?

Stream operators (z.B. cout, derived from `std::ostream`)

```
std::cout << "The_answer_is_" << std::hex << 66 << std::endl;
```

Operator Overloading – usage in STuBS?

Stream operators (z.B. `cout`, derived from `std::ostream`)

```
std::cout << "The_answer_is_" << std::hex << 66 << std::endl;
```

Equivalent in STuBS: `OutputStream`

`OutputStream&` `OutputStream::` `operator<<` `(bool b)` `{...}`
return value namespace overload parameters body

Operator Overloading – usage in STuBS?

Stream operators (z.B. `cout`, derived from `std::ostream`)

```
std::cout << "The_answer_is_" << std::hex << 66 << std::endl;
```

Equivalent in STuBS: `OutputStream`

`OutputStream&` `OutputStream::` `operator<<` `(bool b)` `{...}`
return value namespace overload parameters body

Manipulators:

```
OutputStream& hex(OutputStream&){...}
```

Casting & Type Conversions

`const_cast` `static_cast` `dynamic_cast` `reinterpret_cast`

Adds or removes the attributes `const` or `volatile`

```
const int *x = get();  
int* y = const_cast<int*>(x);
```

Casting & Type Conversions

`const_cast`


`static_cast`

`dynamic_cast`

`reinterpret_cast`

Type check at compile time:

```
D0 d{};  
B *x = &d;  
D0 *a = static_cast<D0*>(x); ✓  
D1 *b = static_cast<D1*>(x); ⚡  
// Runtime: undefined behavior  
  
D1 *c = static_cast<D1*>(a); ⚡  
// Compiler: invalid static_cast from  
// type 'D1*' to type 'D0*'
```



Casting & Type Conversions

`const_cast`

`static_cast`


`dynamic_cast`

`reinterpret_cast`

Type check at compile time:

```
F f{};  
B *x = &f;  
D0 *a = static_cast<D0*>(x); ✓  
D1 *b = static_cast<D1*>(x); ✓  
// Okay: F inherits from D0 and D1
```

```
D1 *c = static_cast<D1*>(a); ⚡  
// Compiler: invalid static_cast from  
// type 'D1*' to type 'D0*'
```



Casting & Type Conversions

`const_cast`

`static_cast`

`dynamic_cast`

`reinterpret_cast`


Type check at runtime (only polymorphic classes):

```
D0 d{};
```

```
B *x = &d;
```

```
D0 *a = dynamic_cast<D0*>(x); ✓
```

```
D1 *b = dynamic_cast<D1*>(x); ⚡ nullptr
```



Casting & Type Conversions

`const_cast` `static_cast` `dynamic_cast` `reinterpret_cast`

„reinterpret“ the bit values

```
char *x = reinterpret_cast<char*>(0xb8000);
```

Casting & Type Conversions

`const_cast` `static_cast` `dynamic_cast` `reinterpret_cast`

„reinterpret“ the bit values

```
char *x = reinterpret_cast<char*>(0xb8000);
```



C-style casts (`int x=(int) malloc(42)`) are supported in C++,
but **should not be used**.

Learning by Doing:
Exercise 0 (C++ Streams)